



## ES Series

Just Solar ES series bi-directional energy-storage inverter is applicable to both on-grid and off-grid PV systems, It can control the flow of energy intelligently. During the day time, the PV plant generates electricity which can be provided to the loads, fed into the grid or charge the battery. The electricity stored can be released when the loads require it during the night. Additionally, the power grid can also charge the storage devices via the inverter.

- Future conception for Solar
- Charge controller and inverter integrated
- Intelligent battery management function
- Longer service life than conventional system
- Capable of being grid-interactive or grid-independent
- Compatible with both Lead-acid and Li-Ion battery
- More security & performance for same costs
- IP65 dust-proof and water-proof rating
- 45 full-load output
- Monitoring inverters freely via computers or mobile phones
- Fanless low-noise design

## Technical Data

	JST-5048D-ES	JST-3648D-ES
<b>Solar</b>		
Max. DC power [W]	5400	4200
Max. DC voltage [V]	580	580
MPPT voltage range [V]	125-550	125-550
Starting voltage [V]	125	125
Max. DC current [A]	15/15	15/15
No. of DC connectors	2	2
No. of MPPTs	2 (can parallel)	2 (can parallel)
DC connector	SUNCLIX / MC4 (optional)	SUNCLIX / MC4 (optional)
<b>Battery</b>		
Battery type	Lead-acid or Li-Ion	Lead-acid or Li-Ion
Battery voltage range [V]	40-60	40-60
Max Discharge power [W]	4600	2300
Charge current [A]	5-50 continuous, programmable	5-50 continuous, programmable
Battery capacity [Ah]	100-500 (depending requirement)	100-500 (depending requirement)
Charging curve	3-stage adaptive with maintenance	3-stage adaptive with maintenance
Battery temperature compensation	Included (Li-Ion)	Included (Li-Ion)
Battery voltage sense	Integrated	Integrated
Current shunt	Integrated	Integrated
<b>AC Output Data</b>		
Normal AC power [W]	4600	3600
Max. AC power [W]	4600	3600
Peak power (Back-up) [W]	1.5x Pnom, 10sec	1.5x Pnom, 10sec
Max. AC current [A]	20	16
Normal AC output	50/60Hz; 230Vac	50/60Hz; 230Vac
AC output range	45-55Hz/55-65Hz; 180-270Vac	45-55Hz/55-65Hz; 180-270Vac
AC output (Back-up)	230Vac ±2%, 50Hz ±0.2%, THDv<3% (linear load)	230Vac ±2%, 50Hz ±0.2%, THDv<3% (linear load)
THDi	<1.5%	<1.5%
Power factor	0.9 leading-0.9 lagging	0.9 leading-0.9 lagging
Grid connection	Single phase	Single phase
<b>Efficiency</b>		
Max. efficiency	97.6%	97.6%
Euro efficiency	>97.0%	>97.0%
MPPT adaptation efficiency	>99.5%	>99.5%
<b>Protection</b>		
Residual current monitoring unit	Integrated	Integrated
Anti-islanding protection	Integrated	Integrated
DC switch (PV)	Integrated	Integrated
AC over current protection	Integrated	Integrated
Insulation monitoring	Integrated	Integrated
<b>Certifications&amp;Standards</b>		
Grid regulation	VDE4105, VDE 0126-1-1+A1, G83/2, G59/2, AS4777.2/3, IEC62109-2	
Safety	IEC62109-1&-2, AS3100, IEC62040-1	
EMC	EN61000-6-1, EN61000-6-2, EN61000-6-3, EN61000-6-4, EN61000-3-11, EN61000-3-12	
<b>General Data</b>		
Dimensions (WxHxD)	516*440*184mm	516*440*184mm
Weight [kg]	30	28
Mounting	Wall bracket	Wall bracket
Ambient temperature range	-20-60°C (>45°C derating)	-20-60°C (>45°C derating)
Relative humidity	0-95%	0-95%
Max. operating altitude	2000m	2000m
Protection degree	IP65	IP65
Topology	Transformerless	Transformerless
Standby losses [W]	<8	<8
Cooling	Nature convection	Nature convection
Noise emission [dB]	<25	<25
Display	LED light & APP	LED light & APP
Communication	USB2.0; RS485; WiFi	USB2.0; RS485; WiFi
Standard warranty [years]	5/10/15/20/25 (optional)	5/10/15/20/25 (optional)